

CAN TAP VALVE

Product Characteristics

economical and practical

Model selection



| | | |
|---------------|--------|--------|
| HS-338/HS-339 | HS-341 | HS-340 |
|---------------|--------|--------|

| Model selection | | | | |
|-----------------|------------------------|--------------|-------------|-----------|
| Model | Refrigerants | Connector A | Connector B | Type |
| HS-338 | R22 | M12 X 1.25 | 1/4 SAE | pin type |
| HS-339 | R134a | M14 X 1.25 | 1/4 SAE | pin type |
| HS-341 | R22 R134a R410A | 7/16-28UNF | 1/4 SAE | stem type |
| HS-340 | universal refrigerants | general type | 1/4 SAE | pin type |

Refrigerant Charging Control Valve

Product Characteristics

Knob

- Aluminum knob, comfortable and durable
- Safe and reliable, energy saving and environmental protection



Model selection



| | | |
|---------|---------|---------|
| HS-1221 | HS-1222 | HS-1223 |
|---------|---------|---------|

| Model selection | | | | |
|-----------------|-----------------|---------------------|-------------|-----------|
| Model | Refrigerants | Connector A | Connector B | Type |
| HS-1221 | R410A R32 | 5/16 SAE(F)(female) | 1/4 SAE | stem type |
| HS-1222 | R22 R404A R407C | 1/4 SAE(F)(female) | 1/4 SAE | stem type |
| HS-1223 | R410A R32 | 5/16 SAE(F)(female) | 5/16 SAE | stem type |

Remarks: Special threads such as 1/2ACME, 1/2ACME left-handed, 5/16SAE left-handed, etc. can be customized