

## ASM130 Sound Level Meter



Wind-proof ball

Condenser microphone

LCD display

LCD backlight

Fast & slow response

Portable

High precision sound sensor

Model	ASM130
Noise (A weighted)	30-130dB
Accuracy	±1.5dB
Resolution	0.1dB
Sampling rate	Fast: 125ms; Slow: 1000ms
Frequency range	31.5Hz-8kHz
Battery	1.5V battery (R03) x 3
Packing	Carton: 40pcs

## ADA30 Digital Anemometer



High precision wind speed sensor

Large backlight LCD display

LCD backlight

Portable

Fast response

High precision temperature sensor

High precision wind speed sensor

Model	ADA30	
Function	Range	Accuracy
Wind Speed Measurement	0-30m/s (Standard)	±(5%rdg+0.5)
	1.4-108Km/h (Reference)	±(5%rdg+15dgts)
	0.7-58knots (Reference)	±(5%rdg+10dgts)
Temperature Measurement	0.8-67mph (Reference)	±(5%rdg+10dgts)
	78-5905ft/min (Reference)	±(5%rdg+180dgts)
Packing	-10°C-50°C	±2°C
	Carton: 40pcs	

## ADM750 Digital Multimeter



Large LCD display

Acousto-optic alarm indicator

Data hold & backlighting

2m drop test

LCD backlight

Data hold

hFE measurement

NCV detection

Temperature measurement

Model	ADM750
DC (V)	1000V
AC (V)	750V
DC(A)	10A
AC(A)	10A
Resistance (Q)	40MΩ
Capacitance (F)	10mF
Packing	Carton: 30pcs

## ADC400 Digital Clamp Meter



High-precision NCV sensor

Audio visual alarm for NCV function

Large LCD display

Data hold & backlighting

Fast capacitance measurement

True RMS measurement

Large LCD display

Audio visual alarm for NCV function

AC voltage frequency measurement

Overcurrent indication

Full-featured false detection protection

Model	ADC400
AC current (A)	400A
AC current frequency (Hz)	50Hz-100Hz
DC voltage (V)	600V
AC voltage (V)	600V
AC voltage frequency (Hz)	10Hz-10KHz
Resistance (Q)	40MΩ
Capacitance(F)	4mF
Temperature measurement (C/°F)	-40-1000°C/-40-1832°F
Packing	Carton: 40pcs